

EUROLITE LED IP T2000 QCL Bar

Weather-proof bar (IP65) with 16 x 10 W 4in1 LED (RGBW), 100 cm

Art. No.: 51914101

GTIN: 4026397572353



The article is no longer in our assortment.

Features:

- Equipped with 16 CREE 4in1 LEDs in the colors red, green, blue and white
- 3, 4, 5, 6, 7 or 10 DMX channels selectable
- For architectural lighting
- Special lenses offer a larger beam angle horizontally than vertically: 10°x40°
- Suitable for external use (IP65)
- Stepless RGBW color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 16 LEDs 10 W high-power 4in1 RGBW (homogenous color mix)
- Strobe effect
- Can be operated in 3; 4; 5; 6; 7; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Flicker-free

Logistic

EAN / GTIN: 4026397572353

Weight: 8,00 kg

Length: 1.07 m

Width: 0.15 m

Height: 0.22 m

- With a beam angle of 40°
- Suitable for outdoor use IP65

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	175 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	16 x 10 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	3; 4; 5; 6; 7; 10
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Fixtures available for:	Light J
Projection:	Flicker-free
Beam angle:	40°
Beam angle (1/2 peak):	40° 10°
Beam angle (1/10 peak):	25° 48°
Housing color:	Black
Dimensions:	Length: 100 cm Depth: 10 cm Height: 18 cm
Weight:	7.25 kg

Scope of delivery:

1 x adapter cable