

EUROLITE LED IP T1000 WW Bar

Weather-proof bar (IP65) with 8 x 5 W warm white LED, length 52 cm

Art. No.: 51914109

GTIN: 4026397589764



The article is no longer in our assortment.

Features:

- Equipped with 8 warm white 5 W CREE LEDs
- For architectural lighting
- Special lenses offer a larger beam angle horizontally than vertically: 10x40°
- Suitable for external use (IP65)
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 8 LEDs 5 W high-power warm white (WW)
- Strobe effect
- Can be operated in 1; 3 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 10°
- Suitable for outdoor use IP65
- Silent operation

Logistic

EAN / GTIN: 4026397589764

Weight: 5,05 kg

Length: 0.58 m

Width: 0.15 m

Height: 0.22 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	8 x 5 W high-power warm white (WW)
Flash rate:	0 - 18 Hz
DMX channels:	1; 3
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Fixtures available for:	Light J
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° 40°
Color temperature:	3000K
Housing color:	Black
Dimensions:	Length: 52.5 cm Depth: 16 cm Height: 9.5 cm
Weight:	4.65 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x adapter cable