

## EUROLITE LED IP T1000 WW Bar

Weather-proof bar (IP65) with 8 x 5 W warm white LED, length 52 cm

Art. No.: 51914109

GTIN: 4026397589764



### Features:

- Equipped with 8 warm white 5 W CREE LEDs
- For architectural lighting
- Special lenses offer a larger beam angle horizontally than vertically: 10x40°
- Suitable for external use (IP65)
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 8 LEDs 5 W high-power warm white (WW)
- Strobe effect
- Can be operated in 1; 3 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 10°
- Suitable for outdoor use IP65
- Silent operation

### Logistic

EAN / GTIN: 4026397589764

Weight: 5,05 kg

Length: 0.58 m

Width: 0.15 m

Height: 0.22 m

## Technical specifications:

|                         |                                                                                                 |
|-------------------------|-------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                          |
| Power consumption:      | 25 W                                                                                            |
| IP classification:      | IP65                                                                                            |
| Power connection:       | Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided) |
| Power output:           | 1 x 3-pin screw plug connector (F) IP                                                           |
| Lamp type:              | LED lamp                                                                                        |
| LED type:               | 8 x 5 W high-power warm white (WW)                                                              |
| Flash rate:             | 0 - 18 Hz                                                                                       |
| DMX channels:           | 1; 3                                                                                            |
| DMX input:              | 1 x 3-pin screw plug connector (M) IP                                                           |
| DMX output:             | 1 x 3-pin screw plug connector (F) IP                                                           |
| Cooling:                | Passive convection cooling                                                                      |
| Control:                | Stand-alone; DMX                                                                                |
| Fixtures available for: | Light J                                                                                         |
| Projection:             | Flicker-free                                                                                    |
| Beam angle:             | 10°                                                                                             |
| Beam angle (1/2 peak):  | 10°<br>40°                                                                                      |
| Color temperature:      | 3000K                                                                                           |
| Housing color:          | Black                                                                                           |
| Dimensions:             | Length: 52.5 cm<br>Depth: 16 cm<br>Height: 9.5 cm                                               |
| Weight:                 | 4.65 kg                                                                                         |
| Noise classification:   | Class 0 (no noise at all)                                                                       |

## Scope of delivery:

1 x adapter cable