

EUROLITE LED IP T-PIX 16 QCL Beam Bar

Weatherproof (IP65) beam bar with RGBL color mixing and pixel control

Art. No.: 51914131

GTIN: 4026397741599



List price: 712.81 €

incl. 19% VAT.

Features:

- 16 LEDs 20 W COB (chip-on-board) 4in1 RGBL
 LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves; color selection preset; program selection adjustable; running light adjustable; program speed adjustable; color macros preset; pulse-width modulation adjustable
- Beam effect
- 33 integrated show programs
- Direct color selection for 16 preset colors
- Can be operated in 3; 4; 5; 10; 14; 22; 38; 48; 64; 70 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; DMX; RDM
- Flicker-free
- RDM For bidirectional communication over the DMX line
- With a beam angle of 3°
- Variable color temperature 2700 K - 6500 K
- With mounting bracket; with omega bracket
- Monochrome OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental
- Silent operation
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397741599

Weight: 12,40 kg

Length: 1.06 m

Width: 0.21 m

Height: 0.17 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 310 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1.5 mm² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	16 x 20 W COB (chip-on-board) 4in1 RGBL
Flash rate:	1 - 25 Hz
DMX channels:	3; 4; 5; 10; 14; 22; 38; 48; 64; 70
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; master/slave function; DMX; RDM
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
DMX features:	RDM For bidirectional communication over the DMX line
DMX fail mode:	Hold; blackout; static; auto
Beam angle:	3°
Beam angle (1/2 peak):	3°
Beam angle (1/10 peak):	6°
Color temperature:	2700K - 6500K adjustable
Housing color:	Black matte
Attachment system:	2x mounting bracket 2x omega bracket
Display type:	1 x monochrome OLED display
Use of brands:	Built with SEETRONIC connector
Material:	Metal, painted
Dimensions:	Length: 100 cm Width: 9.7 cm Height: 16.6 cm
Weight:	10.75 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 2 x mounting bracket
- 1 x plug (male)