

EUROLITE LED IP PAD 9x8W QCL

Weather-proof DMX spot (IP65) with 9 x 8 W 4in1 LED (RGBW)

Art. No.: 51914158

GTIN: 4026397483024



Features:

- 4, 6 or 7 DMX channels selectable for numerous applications
- Equipped with 9 x 8 W 4in1 LED in the colors red, green, blue and white
- For architectural lighting
- Suitable for external use (IP65)
- Compact, matt grey housing
- Functions: Static colors, RGBW color mixture, built-in programs, dimmer, strobe effect, Master/Slave operation
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Infrared remote control in credit card format included in delivery
- Switch-mode power supply, automatic power supply adaption between 100 and 240 volts
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- 9 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Can be operated in 4; 6; 7 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- With a beam angle of 15°
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397483024

Weight: 4,75 kg

Length: 0.30 m

Width: 0.20 m

Height: 0.31 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	9 x 8 W high-power 4in1 RGBW (homogenous color mix)
DMX channels:	4; 6; 7
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	Light´J; LED PC-Control 512
Beam angle:	15°
Beam angle (1/2 peak):	15°
Housing color:	Grey
Dimensions:	Width: 20.5 cm Depth: 12 cm Height: 22.3 cm
Weight:	4.25 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x remote control