

EUROLITE LED IP PAD 24x8W QCL

Weather-proof DMX spotlight (IP65) with 24 x 8 W 4in1 LED (RGBW)

Art. No.: 51914160

GTIN: 4026397461640



The article is no longer in our assortment.

Features:

- Equipped with 24 high-power 8 W 4in1 LEDs in the colors red, green, blue and white
- For architectural lighting
- Suitable for external use (IP65)
- Compact, matt grey housing
- Functions: Static colors, RGBW color mixture, built-in programs, dimmer, strobe effect, Master/Slave operation
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Infrared remote control in credit card format included in delivery
- Switch-mode power supply, automatic power supply adaption between 100 and 240 volts without power selector
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- 24 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Can be operated in 4; 6; 7 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- With a beam angle of 30°
- Suitable for outdoor use IP65
- Silent operation

Logistic

EAN / GTIN: 4026397461640

Weight: 9,80 kg

Length: 0.39 m

Width: 0.23 m

Height: 0.42 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	24 x 8 W high-power 4in1 RGBW (homogenous color mix)
DMX channels:	4; 6; 7
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	Light´ J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Grey
Dimensions:	Width: 29 cm Depth: 14 cm Height: 33 cm
Weight:	8.70 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x adapter cable
1 x remote control
1 x spotlight
1 x user manual
1 x power cord
1 x battery
1 x terminating plug (power)
1 x terminating plug (DMX)