

EUROLITE LED IP PAR 36x1W RGB

Weather-proof DMX spotlight (IP65) with 36 x 1 W LED in red, green and blue

Art. No.: 51914174

GTIN: 4026397434842



Features:

- Equipped with 36 x 1 W LED: 12 x red, 12 x green and 12 x blue
- 3 or 5 DMX channels selectable for numerous applications
- Beam angle approximately 15°
- Locking possibility at the mounting bracket
- Ideal as floor spot via additional bracket
- Stepless RGB color change
- 7 color presets and 4 built-in programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Dimmer and strobe settings via DMX
- Suitable for external use (IP65)
- Perfect for architectural lighting in public places and buildings
- Addressing via control panel with 4-digit LED display
- Control via control panel with display or any regular DMX controller
- Feed-through output allows to power another device
- After every 8 spot the fixtures must have a renewed connection with the power mains
- 36 LEDs 1 W high-power R/G/B (homogenous color mix)
- Strobe effect
- Can be operated in 3; 5 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- With a beam angle of 15°

Logistic

EAN / GTIN: 4026397434842

Weight: 4,30 kg

Length: 0.27 m

Width: 0.27 m

Height: 0.32 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	50 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	36 x 1 W high-power R/G/B (homogenous color mix)
DMX channels:	3; 5
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Fixtures available for:	Light´J; LED PC-Control 512
Beam angle:	15°
Beam angle (1/2 peak):	15°
Housing color:	Black
Dimensions:	Width: 24 cm Depth: 20 cm Height: 32 cm
Weight:	3.85 kg

Scope of delivery:

1 x adapter cable