

EUROLITE LED IP PAR 14x8W QCL

Weather-proof (IP65) spotlight with 4in1 RGBW color mixing and frost filters

Art. No.: 51914178

GTIN: 4026397645217



List price: 415.31 €

incl. 19% VAT.

Features:

- 14 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 18 preset colors
- Can be operated in 2; 3; 4; 8 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397645217

Weight: 8,33 kg

Length: 0.41 m

Width: 0.36 m

Height: 0.35 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 90 W

IP classification: IP65

Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
Equipment:	Frost filter
DMX channels:	2; 3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5900 Hz
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Double bracket
Display type:	Monochrome LCD display
Color:	Black
Dimensions:	Width: 31 cm Depth: 22.5 cm Height: 36.5 cm
Weight:	7.15 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 3 x frost filter
 1 x XLR cable
 2 x knurled screw