

EUROLITE LED IP PAR 12x12W HCL

Weather-proof DMX spotlight (IP65) with 12 x 12 W 6in1 LED (RGBWA+UV)

Art. No.: 51914187

GTIN: 4026397558005



Features:

- Equipped with 12 high-power 12 6in1 LEDs in the colors red, green, blue, amber, white and UV
- 4, 5, 6, 7, 9 or 12 DMX channels selectable
- For architectural lighting
- Suitable for external use (IP65)
- Stepless RGBAW+UV color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 12 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Can be operated in 4; 5; 6; 7; 9; 12 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Flicker-free

Logistic

EAN / GTIN: 4026397558005

Weight: 6,00 kg

Length: 0.28 m

Width: 0.28 m

Height: 0.33 m

- With a beam angle of 20°
- Suitable for outdoor use IP65

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	12 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 5; 6; 7; 9; 12
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	39°
Housing color:	Black
Dimensions:	Width: 27 cm Depth: 16.6 cm Height: 28.4 cm
Weight:	5.55 kg

Scope of delivery:

1 x adapter cable