

EUROLITE LED IP PAR Z60 RGBW

Weather-proof DMX spotlight (IP65) with 60 W RGBW LED and zoom (4 to 32°)

Art. No.: 51914192

GTIN: 4026397602500



The article is no longer in our assortment.

Features:

- Equipped with a 60 W COB LED in the colors red, green, blue and white
- For architectural lighting
- Weather-proof housing (IP65)
- Motorized zoom with 4-74° beam angle
- Stepless RGBW color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- User defined color settings can be set and saved individually
- Internal programs
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with four operating buttons and OLED display
- Ideal as floor spot via additional bracket
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 1 LED 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Strobe effect
- Can be operated in 5; 7; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 4° - 74°

Logistic

EAN / GTIN: 4026397602500

Weight: 5,00 kg

Length: 0.21 m

Width: 0.21 m

Height: 0.35 m

- Suitable for outdoor use IP65

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	85 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	5; 7; 11
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512
Projection:	Flicker-free
Beam angle:	4° - 74°
Beam angle (1/2 peak):	4 - 32°
Beam angle (1/10 peak):	9 - 74°
Housing color:	Black
Dimensions:	Width: 23.4 cm Depth: 17.5 cm Height: 25 cm
Weight:	4.62 kg

Scope of delivery:

1 x adapter cable