

EUROLITE LED IP PAR 7x10W RGBL spot

IP65 spotlight with RGBL LEDs, frost filters and IR remote control

Art. No.: 51914226

GTIN: 4026397718485



Features:

- Two additional frost filters provide a soft, homogeneous light
- 7 LEDs 10 W high-power 4in1 RGBL (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 10°
- Good color rendering index (CRI)
- With double bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

Logistic

EAN / GTIN: 4026397718485

Weight: 4,64 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.33 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	7 x 10 W high-power 4in1 RGBL (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 15° Frost filter 19°
Beam angle (1/10 peak):	20°
Color rendering index (CRI):	81 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 23.4 cm Width: 28 cm Height: 17 cm
Weight:	4.25 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

1 x device
1 x user manual
1 x power cord
1 x remote control
1 x battery
2 x frost filter
2 x screw
1 x mounting bracket