

EUROLITE LED IP PAR 7x15W RGBL spot

IP65 spotlight with RGBL LEDs, frost filters and IR remote control

Art. No.: 51914227

GTIN: 4026397755503



List price: 355.81 €

incl. 19% VAT.

Description:

There is no need to give up the advantages of lime color mixing outdoors. This weatherproof fixture is equipped with seven LEDs featuring color mixing based on red, green, blue, and lime.

This allows not only for vibrant, punchy colors but also for excellent yellow tones and even high-quality white light. The beam angle is 10°, and can be widened using the included frost filters.

Thanks to its passive cooling system, the fixture operates completely fanless and therefore silently, making it ideal for noise-sensitive environments.

Features:

- 7 LEDs 15 W high-power 4in1 RGBL (homogenous color mix)
- Suitable for outdoor use IP65
- Two additional frost filters provide a soft, homogeneous light
- With a beam angle of 10°
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- 36 integrated show programs
- Direct color selection for 15 preset colors
- 3 buttons on the remote control for saving your own settings
- Strobe effect
- Control via IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone
- Flicker-free
- With double bracket
- OLED display

Logistic

EAN / GTIN: 4026397755503

Weight: 4,75 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.34 m

- Mains input and output for power linking up to 8 units
- With pressure compensation membrane
- The device is cooled by passive convection cooling
- With a KENSINGTON LOCK theft protection
- Silent operation
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Application possibility: Standing; suspended; on stand
- Can be operated in 3; 4; 6; 8; 11 CH mode
- Good color rendering index (CRI)

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	7 x 15 W high-power 4in1 RGBL (homogenous color mix)
Flash rate:	0.8 - 22 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 15° Frost filter 19°
Beam angle (1/10 peak):	20°
Color rendering index (CRI):	81 Ra
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 23.4 cm Width: 28 cm Height: 17 cm
Weight:	4.20 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

1 x device
1 x user manual
1 x power cord
1 x remote control
1 x battery
2 x frost filter
2 x screw