

EUROLITE LED IP PAR 12x9W SCL Spot

Weather-proof (IP65) spotlight with 12 x 9 W LED and 7in1 RGB/CW/WW/A/UV color mixing

Art. No.: 51914233

GTIN: 4026397672138



List price: 474.81 €

incl. 19% VAT.

Description:

The IP Par series from Eurolite includes weatherproof fixtures in various sizes and with different color mixing options. The IP Par 12x9W SCL is a bigger fixture with good quality.

Its housing is rated IP65, meaning it can withstand heavy rain. Its special feature is the color mixing, which is based on seven colors: red, green, blue, cool white, warm white, amber, and UV.

This allows it not only to produce colored light, but also very good orange tones, as well as good warm white light through the combination of the two white tones and amber. In addition, blacklight effects are possible. The LEDs used offer a high level of efficiency.

The double bracket allows for floor use, suspended mounting, or stand mounting. Power is supplied via weatherproof T-Con connectors, and power can also be looped through to additional fixtures. For DMX control, 3-pin weatherproof XLR connectors are provided.

Features:

- 12 LEDs 9 W COB (chip-on-board) 7in1 RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- Can be operated in 3; 5; 7; 9; 13 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone
- Flicker-free
- With a beam angle of 15°
- With double bracket

Logistic

EAN / GTIN: 4026397672138

Weight: 5,82 kg

Length: 0.35 m

Width: 0.32 m

Height: 0.20 m

- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 9 W COB (chip-on-board) 7in1 RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	29°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28.5 cm Depth: 15.3 cm Height: 31.35 cm
Weight:	5.20 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2.5 mm
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1.2 m

Battery:

1 x button cell 3.0 V CR2025 lithium manganese
built-in

Scope of delivery:

1 x device
1 x power cord
1 x remote control
1 x battery
1 x user manual