

EUROLITE LED IP PAR 3x9W SCL Spot

Weather-proof (IP65) spotlight with 3 x 9 W LED and 7in1 RGB/CW/WW/A/UV color mixing

Art. No.: 51914235

GTIN: 4026397683981



Description:

The IP Par series from Eurolite includes weatherproof fixtures in various sizes and with different color mixing options. The IP Par 3x9W SCL is a particularly compact fixture with good quality.

Its housing is rated IP65, meaning it can withstand heavy rain. Its special feature is the color mixing, which is based on seven colors: red, green, blue, cool white, warm white, amber, and UV.

This allows it not only to produce colored light, but also very good orange tones, as well as good warm white light through the combination of the two white tones and amber. In addition, blacklight effects are possible. The LEDs used offer a high level of efficiency.

The double bracket allows for floor use, suspended mounting, or stand mounting. Power is supplied via weatherproof T-Con connectors, and power can also be looped through to additional fixtures. For DMX control, 3-pin weatherproof XLR connectors are provided.

Features:

- 3 LEDs 9 W 7in1 RGB/CW/WW/A/UV (homogenous color mix)
- Direct color selection for 28 preset colors
- Can be operated in 3; 5; 7; 9; 13 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65

Logistic

EAN / GTIN: 4026397683981

Weight: 3,20 kg

Length: 0.19 m

Width: 0.19 m

Height: 0.29 m

- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: On stand; suspended

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	35 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	3 x 9 W 7in1 RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX
Fixtures available for:	Light´J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Dimensions:	Width: 21.5 cm Depth: 17.1 cm Height: 24.4 cm
Weight:	3.00 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery