

EUROLITE LED IP Tourlight 80 RGB+WW

Outdoor spotlight (IP65) with RGB/WW color mixing and RGB ambient illumination

Art. No.: 51914246

GTIN: 4026397751789



List price: 415.31 €

incl. 19% VAT.

Features:

- 1 LED 80 W COB (chip-on-board) 4in1 RGB/WW
- 18 LEDs SMD 5050 3in1 RGB
6 segments controlled separately
- Dimmer electronic; color blend stepless
- Wash effect; ambient effect
- 12 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Flicker-free
- With a beam angle of 22°
- With mounting bracket; with omega bracket
- Monochrome OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Architecture; stage; wedding/gala/events; theater; video and photography; rental
- Silent operation
- Application possibility: Suspended; on stand
- Can be operated in 3; 4; 7; 12; 27 CH mode

Logistic

EAN / GTIN: 4026397751789

Weight: 3,00 kg

Length: 0.18 m

Width: 0.19 m

Height: 0.30 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 45 W

IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05RN-F
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse serviceable
Lamp type:	LED lamp
LED type:	1 x 80 W COB (chip-on-board) 4in1 RGB/WW 18 x SMD 5050 3in1 RGB
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 7; 7; 12; 27
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX
Projection:	Flicker-free
PWM frequency:	5900 Hz
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	22°
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	38°
Lamp life:	50000 h
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	Monochrome OLED display
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Width: 19.3 cm Depth: 14.9 cm Height: 26.7 cm
Weight:	2.70 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø11mm
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x omega bracket
 1 x remote control
 1 x battery