

## EUROLITE LED IP Tourlight 80 RGB+WW

Outdoor spotlight (IP65) with RGB/WW color mixing and RGB ambient illumination

Art. No.: 51914246

GTIN: 4026397751789



### Features:

- 1 LED 80 W COB (chip-on-board) 4in1 RGB/WW
- 18 LEDs SMD 5050 3in1 RGB<BR>6 segments controlled separately
- Dimmer electronic; color blend stepless
- Wash effect; ambient effect
- 12 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Flicker-free
- With a beam angle of 22°
- With mounting bracket; with omega bracket
- Monochrome OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Architecture; stage; wedding/gala/events; theater; video and photography; rental
- Silent operation
- Application possibility: Suspended; on stand
- Can be operated in 3; 4; 7; 12; 27 CH mode

### Logistic

EAN / GTIN: 4026397751789

Weight: 3,00 kg

Length: 0.18 m

Width: 0.19 m

Height: 0.30 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 45 W

|                          |                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|
| IP classification:       | IP65                                                                                |
| Protection class:        | Protection class I                                                                  |
| Power connection:        | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug |
| Cable construction:      | 3 x 1.0 mm <sup>2</sup> H05RN-F                                                     |
| Power output:            | IP T-Con (F) mounting version                                                       |
| Fuse:                    | 5 x 20 mm, T 1 A fuse serviceable                                                   |
| Lamp type:               | LED lamp                                                                            |
| LED type:                | 1 x 80 W COB (chip-on-board) 4in1 RGB/WW<br>18 x SMD 5050 3in1 RGB                  |
| Flash rate:              | 0.5 - 24 Hz                                                                         |
| DMX channels:            | 3; 4; 7; 7; 12; 27                                                                  |
| DMX input:               | 3-pin XLR (M) mounting version IP                                                   |
| DMX output:              | 3-pin XLR (F) mounting version IP                                                   |
| Cooling:                 | Passive convection cooling                                                          |
| Control:                 | Stand-alone; IR remote control; DMX                                                 |
| Projection:              | Flicker-free                                                                        |
| PWM frequency:           | 5900 Hz                                                                             |
| DMX fail mode:           | Blackout; hold; full on; static; auto                                               |
| Beam angle:              | 22°                                                                                 |
| Beam angle (1/2 peak):   | 22°                                                                                 |
| Beam angle (1/10 peak):  | 38°                                                                                 |
| Lamp life:               | 50000 h                                                                             |
| Housing color:           | Black                                                                               |
| Attachment system:       | Mounting bracket<br>Omega bracket                                                   |
| Display type:            | Monochrome OLED display                                                             |
| Use of brands:           | Built with SEETRONIC connector                                                      |
| Material:                | Aluminum casting                                                                    |
| Dimensions:              | Width: 19.3 cm<br>Depth: 14.9 cm<br>Height: 26.7 cm                                 |
| Weight:                  | 2.70 kg                                                                             |
| Noise classification:    | Class 0 (no noise at all)                                                           |
| Diameter mounting holes: | 1 x Ø11mm                                                                           |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese<br>built-in                          |

## Scope of delivery:

1 x spotlight  
 1 x user manual  
 1 x power cord  
 1 x omega bracket  
 1 x remote control  
 1 x battery