

EUROLITE LED IP Tourlight 120 WW

Weather-proof LED spotlight (IP65) with warm white 100 W LED, CRI >95

Art. No.: 51914251

GTIN: 4026397661927



The article is no longer in our assortment.

Features:

- Ideal for architectural and front lighting at open air events
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Exact 16 bit resolution at Dimmer
- Dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- Can be operated in 1; 3 CH mode
- The device is cooled by temperature-controlled fan
- Control via DMX; master/slave function
- Flicker-free
- With a beam angle of 12°
- Very high color rendering index (CRI)
- With omega bracket; with double bracket
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Installation; stage; theater; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397661927

Weight: 6,60 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.45 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP65

Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Flash rate:	1 - 20 Hz
DMX channels:	1; 3
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	DMX; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	26°
Color temperature:	3200K
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Omega bracket Double bracket
Dimensions:	Width: 27 cm Depth: 27 cm Height: 30.5 cm
Weight:	5.90 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x omega bracket
 1 x cover