

EUROLITE LED IP Tourlight 200 RGB+WW

Silent IP65 spotlight with RGB+WW color mixture, QuickDMX, CRI >90

Art. No.: 51914252

GTIN: 4026397705072



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- 1 LED 200 W COB (chip-on-board) 4in1 RGB/WW (homogenous color mix)
- Dimmer electronic; color blend stepless
- 9 integrated show programs
- Direct color selection for 27 preset colors
- Can be operated in 3; 4; 5; 6; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; master/slave function
- Flicker-free
- With a beam angle of 30°
- Very high color rendering index (CRI)
- With mounting bracket; with omega bracket; with double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397705072

Weight: 5,50 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.39 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 105 W

IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) 4in1 RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX; IR remote control; master/slave function
Fixtures available for:	Light Captain; Light´J; Colorchief
Projection:	Flicker-free
Beam angle:	30°
Beam angle (1/2 peak):	30°
Beam angle (1/10 peak):	60°
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket Double bracket
Display type:	LCD display
Dimensions:	Width: 25.1 cm Depth: 27.2 cm Height: 32.7 cm Diameter: Ø 18.2 cm
Weight:	4.50 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x omega bracket
 1 x remote control
 1 x battery