

## EUROLITE LED IP Tourlight 200 WW

Silent IP65 spotlight with warm white 200 W LED, QuickDMX, CRI >90

Art. No.: 51914253

GTIN: 4026397705089



### Features:

- Integrated QuickDMX transceiver for wireless DMX control
- 1 LED 200 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- 4 integrated show programs
- Can be operated in 1; 2; 4 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX; IR remote control; master/slave function
- Flicker-free
- With a beam angle of 30°
- Very high color rendering index (CRI)
- With omega bracket; with double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; rental; theater; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397705089

Weight: 5,50 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.39 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 110 W

IP classification: IP65

|                              |                                                                            |
|------------------------------|----------------------------------------------------------------------------|
| Protection class:            | Protection class I                                                         |
| Power connection:            | Mains input via IP T-Con (M) power supply cord with safety plug (provided) |
| Power output:                | IP T-Con (F) mounting version                                              |
| Lamp type:                   | LED lamp                                                                   |
| LED type:                    | 1 x 200 W COB (chip-on-board) warm white (WW)                              |
| DMX channels:                | 1; 2; 4                                                                    |
| DMX input:                   | 3-pin XLR (M) mounting version IP                                          |
| DMX output:                  | 3-pin XLR (F) mounting version IP                                          |
| Cooling:                     | Passive convection cooling                                                 |
| Control:                     | Stand-alone; DMX; QuickDMX; IR remote control; master/slave function       |
| Fixtures available for:      | Light Captain; Colorchief                                                  |
| Projection:                  | Flicker-free                                                               |
| Beam angle:                  | 30°                                                                        |
| Beam angle (1/2 peak):       | 30°                                                                        |
| Beam angle (1/10 peak):      | 60°                                                                        |
| Color temperature:           | 3000K                                                                      |
| Color rendering index (CRI): | 93 Ra                                                                      |
| Housing color:               | Black                                                                      |
| Attachment system:           | Omega bracket<br>Double bracket                                            |
| Display type:                | LCD display                                                                |
| Material:                    | Aluminum casting                                                           |
| Dimensions:                  | Width: 25.1 cm<br>Depth: 27.2 cm<br>Height: 32.7 cm<br>Diameter: Ø 18.2 cm |
| Weight:                      | 4.50 kg                                                                    |
| Noise classification:        | Class 0 (no noise at all)                                                  |
| Diameter mounting holes:     | 2 x Ø18mm; 1 x Ø11mm                                                       |
| Material:                    | Metal, 3 mm                                                                |
| Battery:                     | 1 x button cell 3.0 V CR2025 lithium manganese built-in                    |

## Scope of delivery:

1 x spotlight  
 1 x power cord  
 1 x omega bracket  
 1 x remote control  
 1 x battery  
 1 x user manual