EUROLITE LED IP PAR 9 UV Spot

Weather-proof (IP65) PRO UV spotlight with 9 UV LEDs (365nm), incl. IR remote control

Art. No.: 51914255

GTIN: 4026397697179

Features:

- Minimum visible light
- High output at full intensity
- 9 LEDs 3 W high-power ultra violet (UV)
- Dimmer electronic
- UV effect
- 4 integrated show programs
- Can be operated in 1; 2; 4 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; master/slave function
- With a beam angle of 20°
- With double bracket
- LCD display
- Suitable for outdoor use
- For application areas such as: Architecture; stage; clubs/dancing school; theater; rental; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397697179
Weight: 5,40 kg
Length: 0.38 m
Width: 0.33 m
Heigth: 0.20 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
IP classification:	IP65

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Power output:	IP T-Con (F)
Lamp type:	LED lamp
LED type:	9 x 3 W high-power ultra violet (UV)
Flash rate:	0 - 20 Hz
DMX channels:	1; 2; 4
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; master/slave function
Fixtures available for:	Light Captain; Light´J; Colorchief
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	50
Wavelength:	370 nm
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28.90 cm Depth: 15.25 cm Height: 33.80 cm
Weight:	4.87 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2.5 mm
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.