EUROLITE IP PRO Slim 12x15W RGBL QDMX

Outdoor LED floodlight with RGBL color mixing and wireless DMX transceiver

Art. No.: 51914281

GTIN: 4026397760613











Description:

This weatherproof spotlight offers several special features:
Its housing meets IP65 protection standards, making it suitable for use even in heavy rain.
The color mixing is based on red, green, blue, and lime. This makes the spotlight suitable for colorful light and pastel tones as well as white light in various color temperatures. The beam angle is 6° and can be expanded using the included frost filter.
A special feature is the integrated wireless module for DMX. It supports both Eurolite QuickDMX and CRMX in receiver mode. Furthermore, it functions as a transceiver and can therefore not only receive but also transmit DMX signals, for example for wireless master-slave operation.

The double bracket allows for use on the floor, suspended installations, or mounting on a tripod. Weatherproof T-Con sockets with the option of looping through are available for power supply. The DMX connections are available in both 3-pin and 5-pin versions. The LED cooling is fanless, allowing the spotlight to operate whisper-quietly.

Logistic

EAN / GTIN: 4026397760613
Weight: 6,95 kg
Length: 0.33 m
Width: 0.20 m
Heigth: 0.37 m

Features:

- Transceiver, to be used as transmitter or receiver
- 12 LEDs 15 W SMD 5050 4in1 RGBL (homogenous color mix)
- With a beam angle of 6°
- Additional frost filter provides a wide, soft and homogeneous light
- Suitable for outdoor use IP65
- Variable color temperature 1300 K - 20000 K
- The device is cooled by passive convection cooling
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- With pressure compensation membrane
- With double bracket; with omega bracket

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- 3 buttons on the remote control for saving your own settings
- Control via stand-alone; DMX; RDM; master/slave function; wireless Master/slave function; IR remote control; QDMX(QuickDMX/CRMX compatible)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves adjustable; Dimmer speed (step response) with adjustable response; pulse-width modulation adjustable; color macros preset
- Flicker-free
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; stage; theater; restaurants, bars and hotels; rental
- Silent operation
- Application possibility: Standing; suspended; on stand
- Can be operated in 3; 4; 6; 7; 8; 11 CH mode
- 25 integrated show programs
- Direct color selection for 15 preset colors

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm² H07RN-F
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 15 W SMD 5050 4in1 RGBL (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 3 (HSV hue/saturation/value); 4; 6; 7; 8; 11
DMX input:	3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 5-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; RDM; master/slave function; wireless Master/slave function; IR remote control; QDMX(QuickDMX/CRMX compatible)
Fixtures available for:	GDTF (GrandMA3) 3D
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
DMX fail mode:	Hold; blackout; last action
Beam angle:	6°
Beam angle (1/2 peak):	6° Frost filter 20°
Beam angle (1/10 peak):	15° Frost filter 43°
Color temperature:	1300K - 20000K adjustable
Housing color:	Black matte
Attachment system:	Double bracket Omega bracket

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Display type:	Monochrome OLED display
Use of brands:	Built with SEETRONIC connector
Material:	Aluminum casting
Dimensions:	Width: 31.0 cm Depth: 12.6 cm Height: 31.7 cm
Weight:	6.20 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
1 x remote control
1 x battery
1 x frost filter
4 x screw
1 x omega bracket
1 x declaration of conformity

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.