# EUROLITE LED IP FL-100 COB RGB 120° RC

Outdoor floodlight (IP65) with 100 W COB  LED (RGB) and IR remote control

**Art. No.: 51914614**

GTIN: 4026397552973





## The article is no longer in our assortment.

### Features:

- Add highlights to your house and garden
- Ideal LED luminary for indoor or outdoor use
- Weather-proof housing (IP65)
- Mounting bracket for permanent installation included
- Extremely compact housing in an appealing design
- Equipped with 1 COB RGB LED
- Beam reflection angle of 120°
- Ready for connection via power cord with safety-plug
- Automatic color change or manual program or color selection
- Built-in programs for color change and color fade
- Adjustable program speed and brightness
- Direct color selection for 15 preset colors + white
- Memory function for control programs via the Flash, Strobe, Fade and Smooth buttons of the IR remote control
- 1 LED 100 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control
- With a beam angle of 120°
- Suitable for outdoor use IP65
- Silent operation

  **remote control**
- Operating range up to 7m

### Logistic

EAN / GTIN: 4026397552973
Weight: 5,48 kg
Length: 0.40 m
Width: 0.31 m
Heigth: 0.15 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## Technical specifications:

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 100 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Lamp type: | LED lamp |
| LED type: | 1 x 100 W COB (chip-on-board) 3in1 RGB (homogenous color mix) |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; IR remote control |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Housing color: | Silver |
| Color: | Clear |
| Dimensions: | Width: 28.3 cm<br>Depth: 9.8 cm<br>Height: 38 cm |
| Weight: | 5.08 kg |
| Noise classification: | Class 0 (no noise at all) |
| Range: | Up to 7m |

## Scope of delivery:

1 x spotlight
1 x remote control
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.