EUROLITE LED IP FL-150 3000K

Flat IP54 outdoor floodlight with 196 SMD-LEDs warm white (WW)

Art. No.: 51914787

GTIN: 4026397626162

Features:

- Add highlights to your house and garden
- Extremely flat housing
- 196 LEDs SMD 3030 warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 70°
- With mounting bracket
- Suitable for outdoor use IP54
- Silent operation

Logistic

EAN / GTIN: 4026397626162
Weight: 6,90 kg
Length: 0.45 m
Width: 0.34 m
Heigth: 0.24 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	155 W
IP classification:	IP54
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.9 m
Lamp type:	LED lamp
LED type:	196 x SMD 3030 warm white (WW)
Cooling:	Passive convection cooling

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control:	Plug and play
Beam angle:	70°
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color of light:	Warm white WW <3300 K
Color temperature:	3000K
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Metal
Dimensions:	Width: 42.5 cm Depth: 23 cm Height: 32.5 cm
Weight:	6.35 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x spotlight
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.