

**EUROLITE LED IP FL-20 SMD CW**  
Flat outdoor floodlight (IP66) with white SMD LEDs

**Art. No.: 51915015**  
GTIN: 4026397695816



**Features:**

- 30 LEDs SMD 2835 cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- For application areas such as: Architecture; decoration; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended

**Logistic**

EAN / GTIN: 4026397695816  
Weight: 0,40 kg  
Length: 0.16 m  
Width: 0.07 m  
Heigh: 0.12 m

**Technical specifications:**

|                     |                                          |
|---------------------|------------------------------------------|
| Power supply:       | 230 V AC, 50 Hz                          |
| Power consumption:  | 22 W                                     |
| IP classification:  | IP66                                     |
| Protection class:   | Protection class I                       |
| Power connection:   | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 1.0 mm² H05RN-F                      |
| Cable length:       | Approx. 1 m                              |

|                                  |                                                |
|----------------------------------|------------------------------------------------|
| Lamp type:                       | LED lamp                                       |
| LED type:                        | 30 x SMD 2835 cold white (CW)                  |
| Cooling:                         | Passive convection cooling                     |
| Control:                         | Plug and play                                  |
| Beam angle (1/2 peak):           | 70°                                            |
| Beam angle (1/10 peak):          | 120°                                           |
| Color temperature:               | 6000K                                          |
| Color rendering index (CRI):     | 80 Ra                                          |
| Luminous flux:                   | 1756 lm                                        |
| Housing color:                   | Black matte                                    |
| Attachment system:               | Mounting bracket                               |
| Material:                        | Aluminum casting                               |
| Dimensions:                      | Width: 13 cm<br>Depth: 2.3 cm<br>Height: 10 cm |
| Weight:                          | 0.36 kg                                        |
| Noise classification:            | Class 0 (no noise at all)                      |
| Energy efficiency class (A - G): | F                                              |
| EPREL-Nr:                        | 963751                                         |
| Diameter mounting holes:         | 1 x Ø8mm; 2 x Ø6mm                             |
| Material:                        | Metal, 1.5 mm                                  |

### Scope of delivery:

1 x device  
1 x user manual