

EUROLITE LED IP FL-50 SMD WW
Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915030
GTIN: 4026397695908



Features:

- 64 LEDs SMD 2835 warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- For application areas such as: Architecture; decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Silent operation
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397695908
Weight: 0,70 kg
Length: 0.21 m
Width: 0.07 m
Heigth: 0.17 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	50 W
IP classification:	IP66
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1 m

Lamp type:	LED lamp
LED type:	64 x SMD 2835 warm white (WW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color temperature:	3000K
Color rendering index (CRI):	80 Ra
Luminous flux:	4320 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 25 cm Depth: 2.6 cm Height: 19.2 cm
Weight:	0.63 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	963861
Diameter mounting holes:	1 x Ø8mm; 2 x Ø6mm
Material:	Metal, 1.5 mm

Scope of delivery:

- 1 x device
- 1 x user manual