EUROLITE IP FL-18 BAR UV

Weather-proof LED bar (50 cm) in slimline aluminum cabinet

Art. No.: 51915176

GTIN: 4026397760583









List price: 59.38 €

incl. 19% VAT.

Features:

- 18 LEDs SMD 2835 ultra violet (UV)
- UV effect
- The device is cooled by passive convection cooling
- Sturdy all-metal construction and narrow design
- Control via plug and play
- Flicker-free
- With a beam angle of 15°
- With mounting bracket

Logistic

EAN / GTIN: 4026397760583
Weight: 0,94 kg
Length: 0.51 m
Width: 0.10 m
Heigth: 0.09 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	18 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug built-in
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	18 x SMD 2835 ultra violet (UV)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cooling:	Passive convection cooling
Control:	Plug and play
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	31°
Wavelength:	Ultra violet (UV) 390 nm
Housing color:	Grey matte
Attachment system:	2x mounting bracket
Diameter mounting holes:	2 x Ø6mm
Material:	Aluminum casting, 0.8 mm
Dimensions:	Length: 50 cm Depth: 8.7 cm Height: 4 cm
Weight:	0.84 kg
Photobiological safety:	Risk Group 0 at 0.2 m237.2 lx

Scope of delivery:

1 x device

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.