

EUROLITE LED SLS-9 Hybrid HCL

Flat spotlight with strobe and UV effects, incl. IR remote control

Art. No.: 51915273

GTIN: 4026397603576



The article is no longer in our assortment.

Features:

- Powerful hybrid effect - spot, strobe and UV effect in one device
- Flat version requires minimal space when mounting
- 24 LEDs SMD 5050 cold white (CW) (homogenous color mix)
- 1 LED 15 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- 9 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color macros adjustable; colors preset; program selection; color blend stepless; Dimmer electronic
- Strobe effect; UV effect
- Can be operated in 2; 6; 14; 26 CH mode
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 16°
- With double bracket
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397603576

Weight: 2,44 kg

Length: 0.30 m

Width: 0.28 m

Height: 0.16 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version

Lamp type:	LED lamp
LED type:	24 x SMD 5050 cold white (CW) (homogenous color mix) 1 x 15 W COB (chip-on-board) 4in1 RGBW (homogenous color mix) 9 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 6; 14; 26
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16° 28°
Beam angle (1/10 peak):	39° 54°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 28 cm Depth: 12.2 cm Height: 28.6 cm
Weight:	2.10 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x remote control