

EUROLITE LED SLS-6 UV Floor

DMX controlled UV spot with 6 x 3 W UV LED, incl. IR remote control

Art. No.: 51915282

GTIN: 4026397561708



Features:

- Slim design for space-saving applications
- 6 high-power 3 W UV LEDs
- Built-in auto and music show programs
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Flat, lightweight ABS housing with rubber feet
- Sits flat on the floor or inside a truss
- DMX and power terminals intelligently designed for easy wiring
- Swivel mounting bracket
- Additional bracket for floor use
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 6 LEDs 3 W high-power ultra violet (UV)
- Strobe effect; UV effect
- Can be operated in 2; 4 CH mode
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- With a beam angle of 13°

Logistic

EAN / GTIN: 4026397561708

Weight: 1,63 kg

Length: 0.25 m

Width: 0.24 m

Height: 0.15 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 20 W

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 3 W high-power ultra violet (UV)
DMX channels:	2; 4
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	Light´J; LED PC-Control 512
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	30°
Housing color:	Black
Dimensions:	Width: 23 cm Depth: 11 cm Height: 23 cm
Weight:	1.37 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x remote control