

## EUROLITE LED SLS-30 COB RGBAL Floor

LED floor spot with 5in1 RGBAL color mixing, incl. IR remote control

Art. No.: 51915304

GTIN: 4026397752410



**List price: 129.71 €**

incl. 19% VAT.

### Description:

This fixture demonstrates that lime color mixing is not limited to high-end models. It is based on a COB LED featuring red, green, blue, amber, and lime.

This allows not only for vibrant, punchy colors but also for excellent yellow and orange tones, as well as convincing white light.

### Logistic

EAN / GTIN: 4026397752410

Weight: 1,35 kg

Length: 0.19 m

Width: 0.19 m

Height: 0.24 m

### Features:

- 1 LED 30 W COB (chip-on-board) 5in1 RGBAL (homogenous color mix)
- DMX and power terminals intelligently designed for easy wiring
- Dimmer electronic; color blend stepless; color change adjustable; color fade adjustable
- Wash effect; strobe effect
- 5 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; sound to light via microphone; IR remote control; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 25°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; theater
- Very quiet working noise

- Application possibility: Standing; suspended; on stand
- Can be operated in 3; 5; 7; 10 CH mode
- Good color rendering index (CRI)

## Technical specifications:

|                              |                                                                                                                                                                                                              |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                                                                                                                                       |
| Power consumption:           | 23 W                                                                                                                                                                                                         |
| Protection class:            | Protection class II                                                                                                                                                                                          |
| Power connection:            | Mains input via IEC connector (M) mounting version power supply cord with safety plug                                                                                                                        |
| Power output:                | IEC connector (F) mounting version                                                                                                                                                                           |
| Fuse:                        | 5 x 20 mm, T 1 A fuse replaceable                                                                                                                                                                            |
| Lamp type:                   | LED lamp                                                                                                                                                                                                     |
| LED type:                    | 1 x 30 W COB (chip-on-board) 5in1 RGBAL (homogenous color mix)                                                                                                                                               |
| Flash rate:                  | 0.5 - 23 Hz                                                                                                                                                                                                  |
| DMX channels:                | 3; 5; 5; 7; 10                                                                                                                                                                                               |
| DMX input:                   | 3-pin XLR (M) mounting version                                                                                                                                                                               |
| DMX output:                  | 3-pin XLR (F) mounting version                                                                                                                                                                               |
| Cooling:                     | 1 x low-noise cooling fan                                                                                                                                                                                    |
| Control:                     | Stand-alone; sound to light via microphone; IR remote control; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Fixtures available for:      | Light Captain                                                                                                                                                                                                |
| Projection:                  | Flicker-free                                                                                                                                                                                                 |
| PWM frequency:               | 3900 Hz                                                                                                                                                                                                      |
| DMX fail mode:               | Blackout; hold; full on; static; auto                                                                                                                                                                        |
| Beam angle:                  | 25°                                                                                                                                                                                                          |
| Beam angle (1/2 peak):       | 25°                                                                                                                                                                                                          |
| Beam angle (1/10 peak):      | 80°                                                                                                                                                                                                          |
| Color rendering index (CRI): | 81 Ra                                                                                                                                                                                                        |
| Housing color:               | Black                                                                                                                                                                                                        |
| Attachment system:           | Double bracket                                                                                                                                                                                               |
| Display type:                | 4 digit 7-segment LED display                                                                                                                                                                                |
| USB port:                    | 1 x type A                                                                                                                                                                                                   |
| Diameter mounting holes:     | 1 x Ø11mm                                                                                                                                                                                                    |
| Material:                    | Plastic                                                                                                                                                                                                      |
| Dimensions:                  | Width: 21.5 cm<br>Depth: 12.7 cm<br>Height: 22.85 cm<br>Diameter: Ø 16.8 cm                                                                                                                                  |
| Weight:                      | 1.15 kg                                                                                                                                                                                                      |
| Noise classification:        | Class 1 (very slight noise, suitable for noise-sensitive environments)                                                                                                                                       |

Battery:

1 x button cell 3.0 V CR2025 lithium manganese  
built-in

---

### **Scope of delivery:**

---

1 x spotlight  
1 x power cord  
1 x remote control  
1 x battery  
1 x user manual