

EUROLITE LED SLS-184 RGB 10mm Floor

Slimline LED spot with 184 x 10 mm LED

Art. No.: 51915311

GTIN: 4026397561623



The article is no longer in our assortment.

Features:

- Operable in stand-alone mode or via DMX interface
- DMX512 control possible via any commercial DMX controller (occupies max. 7 channels)
- 4, 5 or 7 DMX channels selectable for numerous applications
- Master/Slave function for synchronous operation with several devices
- Sound-control via built-in microphone
- Microphone-sensitivity adjustable
- Equipped with 184 x 10mm LEDs in red, green and blue
- Flat housing form requires minimal space when rigging
- Designed for hanging or standing installation
- Second mounting bracket for safe standing installation
- Comfortable addressing and setting via control panel with LED display and four operating buttons
- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- Functions: Static colors, RGB color blend, internal programs, dimmer, strobe, sound-control
- Programmable internal program speed and strobe effect
- Ready for connection via included IEC power cord with safety power plug
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- 184 LEDs 10 mm ultra violet (UV)
- Strobe effect
- Can be operated in 4; 5; 7 CH mode
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- With a beam angle of 5°

Logistic

EAN / GTIN: 4026397561623

Weight: 1,89 kg

Length: 0.34 m

Width: 0.32 m

Height: 0.17 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	184 x 10 mm ultra violet (UV)
DMX channels:	4; 5; 7
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512
Beam angle:	5°
Beam angle (1/2 peak):	5°
Beam angle (1/10 peak):	15°
Housing color:	Black
Dimensions:	Width: 26.2 cm Depth: 12.3 cm Height: 28.6 cm
Weight:	1.54 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
DMX connection:	3-pin XLR

Scope of delivery:

1 x remote control