

EUROLITE LED 4C-7 Silent Slim Spot

Silent 4in1 LED spotlight with RGBW color mixture

Art. No.: 51915315

GTIN: 4026397662023



List price: 184.45 €

incl. 19% VAT.

Description:

Silent 4in1 LED spotlight with RGBW color mixing

The Eurolite LED 4C-7 Silent Slim Spot has seven powerful 8-watt RGBW LEDs (4in1) installed. Its RGBW color mixing ensures rich colors. The spotlight does not require a fan as it is cooled purely by convection cooling via cooling fins. This ensures noiseless operation.

You can control the narrow spotlight in master/slave mode and connect up to 32 devices. With the integrated microphone with adjustable microphone sensitivity, the internal show programs can also be played back music-controlled.

Due to the flat housing shape of the LED Slim Spots you only need minimal space during installation.

Features:

- Flat version requires minimal space when mounting
- 7 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Color blend stepless; Dimmer electronic
- Strobe effect
- 9 integrated show programs
- Direct color selection for 19 preset colors
- Can be operated in 3; 4; 5; 6; 9 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX via USB (optional); sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 16°

Logistic

EAN / GTIN: 4026397662023

Weight: 2,87 kg

Length: 0.30 m

Width: 0.26 m

Height: 0.14 m

- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	7 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; QuickDMX via USB (optional); sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal
Dimensions:	Width: 24.5 cm Depth: 11 cm Height: 25.5 cm
Weight:	2.60 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 3 mm
Cable construction:	3 x 1.0 mm² H05VV-F

Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual