

EUROLITE LED Silent Par 6 QCL floor bk

LED floor spot with RGB/WW color mixing

Art. No.: 51915340

GTIN: 4026397713411



Description:

The Silent Par 6 offers several features that are not typically found in this price range. One of its key highlights is the completely fanless and silent operation, making it ideal for noise-sensitive environments.

Its color mixing is based on red, green, blue, and warm white, making it suitable for both colored lighting and basic white light applications.

The flexible double bracket allows for a variety of mounting options, including hanging, stand mounting, or floor placement. In terms of connectivity, the fixture features P-Con power input and output, as well as 3-pin XLR connectors for DMX control.

In addition, the Silent Par 6 includes a Eurolite WDMX USB port, enabling easy upgrades to wireless DMX systems such as Eurolite QuickDMX or CRMX.

Logistic

EAN / GTIN: 4026397713411

Weight: 2,38 kg

Length: 0.21 m

Width: 0.21 m

Height: 0.26 m

Features:

- 14350 lux at 1 m
- 6 LEDs 8 W 4in1 RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- Can be operated in 6; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
- Flicker-free

- With a beam angle of 16°
- With double bracket; with mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	6 x 8 W 4in1 RGB/WW (homogenous color mix)
Flash rate:	1.5 - 30 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
Fixtures available for:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	23500 Hz
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	29°
Housing color:	Black
Attachment system:	Double bracket Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 14.3 cm Width: 17.7 cm Height: 21.1 cm
Weight:	2.15 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 1.5 mm
Cable length:	Approx. 2 m
Color:	Black

Scope of delivery:

1 x spotlight
1 x power cord
1 x XLR cable
1 x user manual