

EUROLITE LED SLS-5 QCL 5x5W Floor 25°

The legendary SLS-5 now with 25° beam angle

Art. No.: 51915382

GTIN: 4026397512601



Features:

- Equipped with 4in1 quadcolor LEDs for homogeneous light output
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, RGBW color blend, internal programs, dimmer, strobe, sound-control, sensitivity
- Further display settings: display on or off, display inverted, default settings
- Operable in stand-alone mode or via DMX
- Master/Slave for parallel operation of several devices
- DMX512 control via regular DMX-controller
- Number of DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Ready for connection with power cord and safety plug
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- Narrow beam angle of 25°
- Can be operated in 6; 4 CH mode
- Control via sound to light via microphone

Logistic

EAN / GTIN: 4026397512601

Weight: 3,35 kg

Length: 0.33 m

Width: 0.27 m

Height: 0.18 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	24 W
--------------------	------

DMX channels:	6; 4
---------------	------

Control:	Sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512
Beam angle (1/2 peak):	25°
Dimensions:	Width: 23 cm Depth: 11 cm Height: 27 cm
Weight:	2.95 kg
DMX channels:	4/6/7
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 W QCL
LED number:	5
Beam angle:	25°
Ventilation fan:	Yes
Dimensions (W x D x H):	230 x 110 x 270 mm

Scope of delivery: