

EUROLITE LED SLS-12 BCL 12x5W Floor

Slimline LED spot with 12 x 5 W 2in1 LED

Art. No.: 51915395

GTIN: 4026397436372



Description:

It is the popular KLS which has paved the path for Slim Line Spots. The KLS was the first successful attempt to replace bulky PAR spots by compact and flat ones - on a bar with 4 spots next to another. As is well known, the concept has been a raving success. As a logic consequence we also transformed the form of single spots - the SLS were born.

Obvious advantages of the SLS: they are slim. Compared to common PAR spots they considerably save space. For this reason they are much more flexible and handy. This is also true for installation, stock ground and transport - for most SLS we sell special cases which are smaller and cheaper than those for PAR spots. In the end, the design can save money.

Meanwhile Eurolite has built up a very rich assortment full of different spots. An assortment which is continuously enlarged. Every delivery finally includes a double bracket enabling an additional use as floor spot. Beside the different sizes of the spots the main differences can be seen in the illuminants. A choice of single LEDs, bicolor, tricolor and quadcolor LEDs is offered.

Features:

- Equipped with bicolor LEDs in white and amber
- Steplessly programmable color temperature and strobe effect
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, color blend, internal programs, dimmer, strobe, sound-control, sensitivity
- Further display settings: display on or off, display inverted, default settings
- Operable in stand-alone mode or via DMX
- Master/Slave for parallel operation of several devices

Logistic

EAN / GTIN: 4026397436372

Weight: 3,80 kg

Length: 0.32 m

Width: 0.37 m

Height: 0.18 m

- DMX512 control via regular DMX-controller
- Number of DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Ready for connection with power cord and safety plug
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- 12 LEDs
- Can be operated in 3; 2 CH mode
- Control via sound to light via microphone

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Power output:	1 x IEC connector (F) mounting version
LED type:	12
Flash rate:	1 - 30 Hz
DMX channels:	3; 2
Control:	Sound to light via microphone
Fixtures available for:	Light J
Beam angle (1/2 peak):	40°
Color:	White
Dimensions:	Width: 28.8 cm Depth: 11 cm Height: 31.2 cm
Weight:	3.30 kg
DMX channels:	2/3/4/5
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED type:	5 W BCL
LED number:	12
Beam angle:	40°
Ventilation fan:	Yes
Dimensions (W x D x H):	288 x 110 x 312 mm

Scope of delivery: