

## EUROLITE LED TL-4 QCL RGB+UV Trusslight

Variable truss light and uplight with bright 4 x 8 W RGB+UV LED

Art. No.: 51915448

GTIN: 4026397658286



### Features:

- Compact and bright
- Perfect for ALUTRUSS 4 point system QUADLOCK
- Folding foot adjustable in 5 steps for flexible placement
- 4 LEDs 8 W high-power 4in1 RGB/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- Can be operated in 3; 4; 8 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- With a beam angle of 13°
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397658286

Weight: 1,70 kg

Length: 0.18 m

Width: 0.18 m

Height: 0.16 m

## Technical specifications:

|                         |                                                                                                                                                                                       |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                |
| Power consumption:      | 15 W                                                                                                                                                                                  |
| Protection class:       | Protection class I                                                                                                                                                                    |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                      |
| Lamp type:              | LED lamp                                                                                                                                                                              |
| LED type:               | 4 x 8 W high-power 4in1 RGB/UV (homogenous color mix)                                                                                                                                 |
| Flash rate:             | 0 - 20 Hz                                                                                                                                                                             |
| DMX channels:           | 3; 4; 8                                                                                                                                                                               |
| DMX input:              | 1 x USB, type A<br>1 x 3-pin XLR (M) mounting version                                                                                                                                 |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                                                                                    |
| Cooling:                | Passive convection cooling                                                                                                                                                            |
| Control:                | DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone |
| Fixtures available for: | LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                     |
| Beam angle:             | 13°                                                                                                                                                                                   |
| Beam angle (1/2 peak):  | 13°                                                                                                                                                                                   |
| Beam angle (1/10 peak): | 30°                                                                                                                                                                                   |
| Housing color:          | Black                                                                                                                                                                                 |
| Attachment system:      | M10 thread                                                                                                                                                                            |
| Display type:           | Monochrome 4 digit 7-segment LED display                                                                                                                                              |
| Transport aid:          | Rubber feet                                                                                                                                                                           |
| Dimensions:             | Length: 15.5 cm<br>Width: 14.5 cm<br>Height: 13.0 cm                                                                                                                                  |
| Weight:                 | 1.56 kg                                                                                                                                                                               |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                                                             |
| Photobiological safety: | Risk Group 0                                                                                                                                                                          |
| Cable construction:     | 3 x 0.75 mm² H05VV-F                                                                                                                                                                  |
| Cable length:           | Approx. 1.1 m                                                                                                                                                                         |
| Color:                  | Black                                                                                                                                                                                 |

## Scope of delivery:

1 x spotlight  
1 x power cord  
1 x remote control  
1 x user manual