

## EUROLITE LED TL-3 TCL 3x3W Trusslight

Spot with 3 x 3 W RGB LEDs, mounting hole and IR remote control

Art. No.: 51915450

GTIN: 4026397509410



### Features:

- Compact and bright, making it perfect for truss installation
- Equipped with 3 x 3 W 3in1LED in the colors red, green and blue
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Convenient control possible via IR remote control (optional accessory)
- 3, 5 or 8 DMX channels selectable
- Functions: static colors, stepless RGB color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Sound-controlled via built-in microphone
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Ideal for booth construction, stages and any kind of truss
- Ideal for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
- Hanging as well as standing installation possible
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 3 LEDs 3 W high-power 3in1 RGB (homogenous color mix)
- Can be operated in 3; 5; 8 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control (optional); stand-alone; DMX; sound to light via microphone
- With a beam angle of 16°

### Logistic

EAN / GTIN: 4026397509410

Weight: 1,00 kg

Length: 0.16 m

Width: 0.15 m

Height: 0.15 m

## Technical specifications:

|                         |                                                                                                  |
|-------------------------|--------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                           |
| Power consumption:      | 12.00 W                                                                                          |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output:           | 1 x IEC connector (F) mounting version                                                           |
| Lamp type:              | LED lamp                                                                                         |
| LED type:               | 3 x 3 W high-power 3in1 RGB (homogenous color mix)                                               |
| Flash rate:             | 0 - 30 Hz                                                                                        |
| DMX channels:           | 3; 5; 8                                                                                          |
| Cooling:                | Passive convection cooling                                                                       |
| Control:                | IR remote control (optional); stand-alone; DMX; sound to light via microphone                    |
| Fixtures available for: | Light´J; LED PC-Control 512; Light Captain                                                       |
| Beam angle:             | 16°                                                                                              |
| Beam angle (1/2 peak):  | 16°                                                                                              |
| Beam angle (1/10 peak): | 34°                                                                                              |
| Housing color:          | Black                                                                                            |
| Dimensions:             | Width: 12.1 cm<br>Depth: 10.8 cm<br>Height: 10.4 cm                                              |
| Weight:                 | 0.90 kg                                                                                          |
| DMX connection:         | 3-pin XLR                                                                                        |

## Scope of delivery: