

EUROLITE LED PST-40 QCL Spot

LED spotlight with RGBW color mixing, IR remote control and 2 frost filters

Art. No.: 51916170

GTIN: 4026397710625



List price: 213.01 €

incl. 19% VAT.

Description:

This compact fixture is a powerful pinspot with versatile applications. A 40 W LED with RGBW color mixing produces a precise, narrow 4° beam, making it ideal for applications such as illuminating mirror balls.

Thanks to its fanless design, the unit operates completely silently and is well suited for noise-sensitive environments. The included frost filters allow the beam angle to be expanded to 20° or even 80°, enabling the fixture to be used as a compact spot or floodlight.

Despite its small size, the fixture offers extensive connectivity: P-Con power input and output, 3-pin XLR connectors for DMX control, and a WDMX USB port for easy upgrades to wireless DMX systems such as QuickDMX or CRMX.

Features:

- Two additional frost filters provide a soft, homogeneous light
- 1 LED 40 W 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function
- Flicker-free

Logistic

EAN / GTIN: 4026397710625

Weight: 2,22 kg

Length: 0.19 m

Width: 0.17 m

Height: 0.28 m

- With a beam angle of 4°
- With double bracket
- OLED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand
- **remote control**
- 24 buttons on the remote control for saving your own settings

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	36 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 40 W 4in1 RGBW (homogenous color mix)
Flash rate:	0.8 - 22 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4° Frost filter 20° Frost filter 80°
Beam angle (1/10 peak):	8°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Material:	Plastic; metal
Dimensions:	Length: 12 cm Width: 17 cm Height: 22.5 cm
Weight:	1.98 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø11mm; 3 x Ø2mm
Material:	Metal, 2 mm
Cable construction:	3 x 1.0 mm² H05VV-F

Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Material:	Plastic, 3 mm
Dimensions:	Width: 12 cm Height: 10.8 cm

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
1 x battery
2 x frost filter
1 x user manual