

EUROLITE LED IP PST-40 QCL Spot

Weather-proof LED spotlight (IP65) with 40 W LED, incl. IR remote control, frost filter & ground stake

Art. No.: 51916175

GTIN: 4026397710724



Description:

This compact and weatherproof fixture combines high performance with versatile applications. As a pinspot, it produces a precise, narrow 4° beam thanks to its 40 W RGBW LED, making it ideal for illuminating mirror balls or for accent lighting in architectural applications.

Its fanless design ensures completely silent operation, making it suitable even for highly noise-sensitive environments. With the included frost filter, the beam angle can be expanded to 20°, allowing the fixture to also function as a compact, weatherproof spotlight.

For professional use, the fixture features T-Con connectors for power input and daisy-chaining, as well as weatherproof 3-pin XLR connectors for DMX control. The connections are implemented as fixed cables, allowing multiple fixtures to be directly linked in architectural setups or extended using standard IP-rated XLR and T-Con cables.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 LED 40 W 4in1 RGBW (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone

Logistic

EAN / GTIN: 4026397710724

Weight: 2,52 kg

Length: 0.24 m

Width: 0.20 m

Height: 0.24 m

- Flicker-free
- Easy installation
- With a beam angle of 4°
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	36 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug included
Power output:	IP T-Con (F)
Lamp type:	LED lamp
LED type:	1 x 40 W 4in1 RGBW (homogenous color mix)
Flash rate:	0.8 - 22 Hz
Equipment:	Frost filter
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) IP
DMX output:	3-pin XLR (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Setup:	Easy installation
Beam angle:	4°
Beam angle (1/2 peak):	4° Frost filter 20°
Beam angle (1/10 peak):	8°
Color temperature:	7400K
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 11 cm Width: 14.3 cm Height: 19.6 cm
Weight:	2.23 kg

Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	3 x Ø11mm; 2 x Ø6mm
Material:	Aluminum, 2 mm
Cable construction:	3 x 1.0 mm ² H07RN-F
Cable length:	Approx. 1.2 m
Material:	Plastic
Color:	Black
Dimensions:	Height: 16 cm
Material:	Plastic, 3 mm
Dimensions:	Diameter: Ø 10.3 cm
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

Scope of delivery:

1 x spotlight
 1 x power cord
 1 x stake
 1 x frost filter
 1 x remote control
 1 x battery
 1 x screw
 2 x washer
 1 x user manual