

EUROLITE LED PAR-64 RGBA 10mm Short sil

PRO spotlight as LED DMX model

Art. No.: 51916400

GTIN: 4026397389296



Description:

Warm up!

Eurolite now offers a new series to its favorite LED PAR-64 Spots including amber colored LEDs in addition to the primary colors red, green and blue. By adding the color amber, which is composed of red and yellow, the ordinary RGB color mixing can be "warmed up" individually with the fourth color. You will have wider range of opportunities for lighting design: warm colors create a cozy atmosphere in bars, lounges or at exhibition stands - child's play for the RGBA-Spots!

Features:

- 4 or 6 DMX channels selectable for numerous applications
- Equipped with 177 x 10 mm LEDs: 30 x red, 48 x green, 54 x blue and 45 x amber
- Sound-control via built-in microphone
- Beam angle approximately 36°
- Locking possibility at the mounting bracket
- Addressing and setting via control panel with LED display
- Preset (internal programs)
- RGBA color change
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Dimmer and Strobe settings via DMX
- Ready for connection with power cord and plug
- Also available as floor spot version
- Available in silver or black
- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation

Logistic

EAN / GTIN: 4026397389296

Weight: 2,65 kg

Length: 0.25 m

Width: 0.25 m

Height: 0.38 m

- DMX512 control via regular DMX controller
- Can be operated in 6; 4 CH mode
- Control via stand-alone; DMX

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	27 W
Lamp type:	LED lamp
DMX channels:	6; 4
Control:	Stand-alone; DMX
Fixtures available for:	Light´J; LED PC-Control 512
Beam angle (1/2 peak):	36°
Housing color:	Silver
Dimensions:	Width: 26 cm Depth: 27 cm Height: 39 cm
Weight:	2.30 kg
DMX channels:	4/6
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
LED number:	177
LED type:	10 mm
Beam angle:	36°
Dimensions:	260 x 270 x 390 mm

Scope of delivery: