

## EUROLITE LED RETRO 6 Bar ABL

Warm white blinder with additional colored LEDs for atmospheric lighting

Art. No.: 51916645

GTIN: 4026397755725



**List price: 296.31 €**

incl. 19% VAT.

### Description:

This 100 cm bar combines modern lighting technology with a distinctive retro look. Six powerful LED strips produce a very warm, almost orange-toned white light.

Each strip is equipped with a 60 W LED and can be controlled individually. The reflective sections between them are illuminated by a total of 120 RGB LEDs, which are divided into 12 segments and can be controlled individually.

A range of DMX modes is available. In the most advanced mode, all elements can be controlled individually, while reduced modes still offer a wide variety of effects even with smaller DMX controllers.

The series is complemented by a matching spot fixture that delivers the same effects in a different form factor.

### Logistic

EAN / GTIN: 4026397755725

Weight: 5,85 kg

Length: 1.05 m

Width: 0.17 m

Height: 0.24 m

### Features:

- 6 LEDs 60 W COB (chip-on-board) amber (A)<BR>LEDs controlled separately
- 120 LEDs 0.1 W SMD 5050 3in1 RGB (homogenous color mix)<BR>10 segments controlled separately
- Blinder effect; strobe effect
- With a beam angle of 120°
- Silent operation
- Flicker-free
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- 3 integrated show programs
- With bracket for floor use; with omega bracket

- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile use; stage; theater; mobile djs / entertainer; restaurants, bars and hotels; rental
- Application possibility: Standing; suspended
- Can be operated in 12; 16; 43 CH mode

## Technical specifications:

|                         |                                                                                                                                                                             |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                      |
| Power consumption:      | 200 W                                                                                                                                                                       |
| Protection class:       | Protection class I                                                                                                                                                          |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug                                                                                        |
| Cable construction:     | 3 x 1.5 mm² H05VV-F                                                                                                                                                         |
| Power output:           | P-Con (grey), mounting version                                                                                                                                              |
| Lamp type:              | LED lamp                                                                                                                                                                    |
| LED type:               | 6 x 60 W COB (chip-on-board) amber (A)<br>120 x 0.1 W SMD 5050 3in1 RGB (homogenous<br>color mix)                                                                           |
| Flash rate:             | 0.8 - 20 Hz                                                                                                                                                                 |
| DMX channels:           | 12; 16; 43                                                                                                                                                                  |
| DMX input:              | 3-pin XLR (M) mounting version<br>5-pin XLR (M) mounting version                                                                                                            |
| DMX output:             | 3-pin XLR (F) mounting version<br>5-pin XLR (F) mounting version                                                                                                            |
| Cooling:                | 2 x temperature-controlled fan                                                                                                                                              |
| Control:                | Stand-alone; sound to light via microphone; DMX;<br>QuickDMX via USB (optional); W-DMX by<br>wireless solution via USB (optional); CRMX by<br>LumenRadio via USB (optional) |
| Fixtures available for: | Light Captain                                                                                                                                                               |
| Projection:             | Flicker-free                                                                                                                                                                |
| PWM frequency:          | 4000 Hz                                                                                                                                                                     |
| Beam angle:             | 120°                                                                                                                                                                        |
| Beam angle (1/2 peak):  | 120°                                                                                                                                                                        |
| Beam angle (1/10 peak): | 120°                                                                                                                                                                        |
| Color temperature:      | 1800K                                                                                                                                                                       |
| Housing color:          | Black                                                                                                                                                                       |
| Attachment system:      | Bracket for floor use<br>Omega bracket                                                                                                                                      |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                               |
| USB port:               | Type A                                                                                                                                                                      |
| Use of brands:          | Built with SEETRONIC connector                                                                                                                                              |
| Material:               | Metal                                                                                                                                                                       |
| Dimensions:             | Width: 100.0 cm<br>Depth: 14.0 cm<br>Height: 15.0 cm                                                                                                                        |
| Weight:                 | 5.10 kg                                                                                                                                                                     |

Noise classification:

Class 0 (no noise at all)

---

**Scope of delivery:**

---

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x omega bracket