

EUROLITE LED DMF-3 Hybrid Flower Effect

Effect spotlight with flower and strobe effect, incl. IR remote control

Art. No.: 51918562

GTIN: 4026397673180



Description:

Effect light with flower and stroboscope effect, incl. IR remote control

The EUROLITE LED DMF-3 Hybrid Flower Effect is perfect for solo entertainers, small bands and party rooms. Behind the two lenses it is equipped with a total of 12 LEDs in the colors red, green, blue, amber, white and UV.

The two strobe rings of the effect have 36 RGB LEDs, which create fast and dynamic strobe effects. The flower and strobe LEDs can be controlled separately.

You can control them either by DMX, by music control via the microphone with adjustable sensitivity, via the master/slave function or with the included infrared remote control. Four integrated show programs are available in auto and music mode.

Addressing and settings are made via the integrated control unit with 4-digit LED display.

The scope of delivery also includes a swivelling mounting bracket and an additional bracket for setting up the light effect directly on the floor.

Logistic

EAN / GTIN: 4026397673180

Weight: 1,91 kg

Length: 0.28 m

Width: 0.20 m

Height: 0.16 m

Features:

- 2 disco balls fill the room with innumerable colorful beams
- 2 additional strobe rings with 36 RGB LEDs provide fast, dynamic strobe effects
- 4 integrated show programs
- Direct color selection for 24 preset colors
- Can be operated in 8; 22 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Flicker-free
- With a beam angle of 80°
- With double bracket

- Mains input and output for power linking up to 8 units
- For application areas such as: Party room; decoration
- Silent operation
- Application possibility: Standing; suspended; on stand

light effect

- 12 LEDs high-power R/G/B/W/A/UV
- Multi beam effect; flower effect

strobes

- 36 LEDs 0.2 W 3in1 RGB
- Strobe effect

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	8; 22
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	80°
Beam angle (1/2 peak):	80°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Width: 25.0 cm Depth: 14.6 cm Height: 17.9 cm
Weight:	1.70 kg
Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
LED type:	12 x high-power R/G/B/W/A/UV
LED type:	36 x 0.2 W 3in1 RGB
Flash rate:	0 - 20 Hz

Scope of delivery:

- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery