

EUROLITE LED GF-100 Gobo Flower

Bright gobo flower with rotating, colorful faceted mirror and varied gobos

Art. No.: 51918587

GTIN: 4026397739909



The article is no longer in our assortment.

Features:

- Flower mirror multiplies the gobos and lets them dance in the room
- 1 LED 100 W COB (chip-on-board) cold white (CW)
- Focus manual
- Dimmer electronic
- Gobo effect; flower effect; strobe effect
- Gobo wheel with static gobos, 11 gobos
shake effect
- 10 integrated show programs
- Can be operated in 2; 4; 5 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 80°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; on stand

Logistic

EAN / GTIN: 4026397739909

Weight: 5,20 kg

Length: 0.41 m

Width: 0.32 m

Height: 0.21 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	140 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm ² H05VV-F
Power output:	1 x P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 30 Hz
Equipment:	Focus manual
Gobos:	Gobo wheel with static gobos, 11 gobos Shake effect
DMX channels:	2; 4; 5
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	3 x temperature-controlled fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
DMX fail mode:	Blackout; hold
Beam angle:	80°
Beam angle (1/2 peak):	80°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Diameter mounting holes:	3 x Ø12mm
Material:	Metal
Dimensions:	Width: 32.0 cm Depth: 23.5 cm Height: 19.5 cm
Weight:	4.50 kg
Noise classification:	Class 2 (slight noise) depending on mode used

Scope of delivery:

1 x light effect
1 x user manual
1 x power cord