EUROLITE GoFlow 100

Extremely bright gobo flower with separate color/gobo wheel and 2 rotation functions

Art. No.: 51918591

GTIN: 4026397724486

Features:

- 1 LED 100 W COB (chip-on-board) cold white (CW)
- Gobo wheel with rotating gobos; color wheel
- Dimmer electronic
- Flower effect; gobo effect; strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 8 gobos
gobos changeable
- Slot-in gobo system for easy gobo replacement
- 24 integrated show programs
- Can be operated in 2; 6; 8 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With a beam angle of 80°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; stage; mobile djs / entertainer; restaurants, bars and hotels; rental
- Very quiet working noise
- Application possibility: Suspended; on stand
- 2 buttons on the remote control for saving your own settings

Logistic

EAN / GTIN: 4026397724486

Weight: 6,05 kg

Length: 0.46 m

Width: 0.28 m

Heigth: 0.23 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 2.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Flash rate:	0.5 - 25 Hz
Equipment:	Gobo wheel with rotating gobos; color wheel
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 8 gobos Outside diameter 23.80mm Image diameter 14mm Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	2; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Colorchief; Light Captain
Beam angle:	80°
Beam angle (1/2 peak):	80°
Color temperature:	8000K
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 40.5 cm Width: 22.5 cm Height: 26 cm
Weight:	5.55 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Diameter mounting holes:	1 x Ø13mm
Material:	Metal, 2 mm
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Scope of delivery:

1 x device
1 x power cord
1 x remote control
1 x battery
6 x gobos
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.