

EUROLITE LED B-200 Hypno Double Ball Beam Effect

LED beam effect with RGBW color mixing and 8 RGB hypno rings

Art. No.: 51918826

GTIN: 4026397727159



List price: 355.81 €

incl. 19% VAT.

Features:

- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- 8 LEDs 10 W SMD 5050 4in1 RGBW
- 96 LEDs 0.2 W SMD 5050 3in1 RGB
- Dimmer electronic; color change; color fade; color blend; Rotation speed adjustable; Rotation direction adjustable
- Multi beam effect; strobe effect
- 2 integrated show programs
- Can be operated in 17; 24 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone
- Flicker-free
- With omega bracket; with mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended
screw
- M6 thread

Logistic

EAN / GTIN: 4026397727159

Weight: 5,60 kg

Length: 0.45 m

Width: 0.26 m

Height: 0.38 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	100 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Lamp type:	LED lamp
LED type:	8 x 10 W SMD 5050 4in1 RGBW 96 x 0.2 W SMD 5050 3in1 RGB
Max. PAN movement:	540°
Speed:	Forward/backward
Flash rate:	0 - 20 Hz
DMX channels:	17; 24
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone
Fixtures available for:	Light Captain
Projection:	Flicker-free
Illuminance in Lux (lx):	Red (R) 1m: 4812 lx, 3m: 1146 lx, 6m: 271 lx Green (G) 1m: 8250 lx, 3m: 2434 lx, 6m: 723 lx Blue (B) 1m: 3015 lx, 3m: 604 lx, 6m: 153 lx Cold white (CW) 1m: 14513 lx, 3m: 3918 lx, 6m: 817 lx
Housing color:	Black
Attachment system:	Omega bracket Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal; plastic
Dimensions:	Width: 40.0 cm Depth: 21.0 cm Height: 32.0 cm
Weight:	5.00 kg
Noise classification:	Class 2 (slight noise)
Cable construction:	3 x 0.75 mm² H05VV-F
Diameter mounting holes:	4 x Ø5mm; 4 x Ø8mm; 2 x Ø8mm; 1 x Ø10mm
Material:	Metal, 2 mm
Thread:	M6 thread x 12 mm

Scope of delivery:

1 x light effect
 1 x power cord
 2 x omega bracket
 2 x screw
 1 x user manual