

EUROLITE LED B-40 HCL Beam Effect MK2

LED beam effect with RGBWA+UV color mixing, incl. remote-control

Art. No.: 51918952

GTIN: 4026397713183



Features:

- 5 LEDs 10 W 6in1 RGBWA/UV<BR> segments controlled separately
- Rotation speed adjustable; Dimmer electronic; color blend stepless
- Multi beam effect; strobe effect
- 8 integrated show programs
- Can be operated in 3; 12; 23 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397713183  
Weight: 6,05 kg  
Length: 0.41 m  
Width: 0.40 m  
Heigh: 0.52 m

Technical specifications:

|                    |                                                                                                  |
|--------------------|--------------------------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                                                                           |
| Power consumption: | 56 W                                                                                             |
| Protection class:  | Protection class I                                                                               |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |

|                          |                                                                                                                                                                                                              |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power output:            | IEC connector (F) mounting version                                                                                                                                                                           |
| Fuse:                    | T 1.6 A fuse replaceable                                                                                                                                                                                     |
| Lamp type:               | LED lamp                                                                                                                                                                                                     |
| LED type:                | 5 x 10 W 6in1 RGBWA/UV                                                                                                                                                                                       |
| Flash rate:              | 0 - 20 Hz                                                                                                                                                                                                    |
| DMX channels:            | 3; 12; 23                                                                                                                                                                                                    |
| DMX input:               | 1 x 3-pin XLR (M) mounting version                                                                                                                                                                           |
| DMX output:              | 1 x 3-pin XLR (F) mounting version                                                                                                                                                                           |
| Cooling:                 | Passive convection cooling                                                                                                                                                                                   |
| Control:                 | IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function |
| Fixtures available for:  | Light´ J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                                                                                |
| Housing color:           | Black matte                                                                                                                                                                                                  |
| Attachment system:       | Omega bracket                                                                                                                                                                                                |
| Display type:            | Monochrome 4 digit 7-segment LED display                                                                                                                                                                     |
| Material:                | Metal; plastic                                                                                                                                                                                               |
| Dimensions:              | Length: 32.00 cm<br>Width: 32.00 cm<br>Height: 39.00 cm                                                                                                                                                      |
| Weight:                  | 4.22 kg                                                                                                                                                                                                      |
| Noise classification:    | Class 2 (slight noise)                                                                                                                                                                                       |
| Cable construction:      | 3 x 1.0 mm² H05VV-F                                                                                                                                                                                          |
| Cable length:            | Approx. 1.5 m                                                                                                                                                                                                |
| Diameter mounting holes: | 1 x Ø13mm; 4 x Ø4mm                                                                                                                                                                                          |
| Material:                | Metal, 3 mm                                                                                                                                                                                                  |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                                                                                      |

## Scope of delivery:

1 x light effect  
 1 x power cord  
 1 x omega bracket  
 1 x remote control  
 4 x screw  
 4 x washer  
 1 x user manual