



The article is no longer in our assortment.

Features:

- Controller and power supply unit for LED light tubes
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Can be operated in 5; 7; 32; 210; 468; 480 CH mode
- Control via stand-alone; Art-Net; DMX; sound to light via microphone; master/slave function
- LCD display

Logistic

EAN / GTIN: 4026397532425
Weight: 3,65 kg
Length: 0.40 m
Width: 0.35 m
Heigh: 0.12 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	240 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
DMX channels:	5; 7; 32; 210; 468; 480
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; Art-Net; DMX; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512

Display type:	LCD display
Output:	24 V DC;
Dimensions:	Width: 29 cm Depth: 30 cm Height: 6 cm
Weight:	3.20 kg

Scope of delivery: