



Features:

- Controller and power supply unit for 4 LED light tubes
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Can be operated in 5; 7; 14; 84; 192; 312 CH mode
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- 3 digit 7-segment LED display

Logistic

EAN / GTIN: 4026397502237
Weight: 2,40 kg
Length: 0.37 m
Width: 0.31 m
Heigh: 0.10 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95.00 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
DMX channels:	5; 7; 14; 84; 192; 312
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512

Maximum connection:	4 tubes
Display type:	3 digit 7-segment LED display
Output:	24 V DC;
Dimensions:	Width: 24 cm Depth: 29 cm Height: 6 cm
Weight:	2.05 kg

Scope of delivery:

1 x device
1 x user manual
1 x power cord