



The article is no longer in our assortment.

Features:

- Controller and power supply unit for 8 LED light tubes
- Pixels individually controllable via MADRIX
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Can be operated in 5; 7; 26 CH mode
- Control via stand-alone; Art-Net; DMX; sound to light via microphone; master/slave function
- LCD display
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397543292
Weight: 3,90 kg
Length: 0.40 m
Width: 0.35 m
Height: 0.12 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	350 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
DMX channels:	5; 7; 26
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version

Control:	Stand-alone; Art-Net; DMX; sound to light via microphone; master/slave function
Fixtures available for:	LED PC-Control 512
Display type:	LCD display
Output:	12 V DC;
Dimensions:	Width: 27 cm Depth: 32 cm Height: 7.6 cm
Weight:	3.45 kg

Scope of delivery: