EUROLITE LED BP-16 Panel

LED beam panel with 4 x 4 matrix and 7 W LEDs

Art. No.: 51930275

GTIN: 4026397506150









The article is no longer in our assortment.

Features:

- Equipped with 16 white 7 W LEDs
- 5 or 16 DMX channels selectable
- Each LED can be controlled individually
- Second mounting bracket for different rigging possibilities
- Suitable for pixel mapping applications
- Functions: Built-in programs, dimmer and strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Sound-controlled via built-in microphone
- Adjustable microphone sensitivity via Control Board
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 Volts
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power up to 8 devices
- DMX control via every standard DMX controller
- 16 LEDs 7 W high-power cold white (CW)
- Beam effect
- Can be operated in 5; 16 CH mode
- Control via stand-alone; DMX
- With a beam angle of 1.5°

Logistic

EAN / GTIN: 4026397506150
Weight: 8,20 kg
Length: 0.49 m
Width: 0.23 m
Heigth: 0.52 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150.00 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey), mounting version
Lamp type:	LED lamp
LED type:	16 x 7 W high-power cold white (CW)
DMX channels:	5; 16
Control:	Stand-alone; DMX
Fixtures available for:	Light´J
Beam angle:	1.5°
Beam angle (1/2 peak):	1.5°
Housing color:	Black
Dimensions:	Width: 14.3 cm Depth: 39.9 cm Height: 39.9 cm
Weight:	6.60 kg
DMX channels:	5/16
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Flash-rate:	30 Hz
LED type:	7 W, white
LED number:	16
Beam angle:	1.5°
Dimensions (L x W x H):	143 x 399 x 399 mm

Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.