

EUROLITE LED CBB-6 COB RGB Bar

LED light effect bar with RGB color mixing, incl. IR remote control

Art. No.: 51930279

GTIN: 4026397653762



List price: 355.81 €

incl. 19% VAT.

Features:

- 6 LEDs 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- Can be operated in 2; 3; 5; 9; 18; 21 CH mode
- The device is cooled by low-noise cooling fan
- Control via IR remote control; sound to light via microphone; master/slave function; DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 38°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; video and photography
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397653762

Weight: 7,10 kg

Length: 0.72 m

Width: 0.24 m

Height: 0.21 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 100 W

Fuse: T 2 A fuse replaceable

Lamp type:	LED lamp
LED type:	6 x 30 W COB (chip-on-board) 3in1 RGB (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5; 9; 18; 21
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	IR remote control; sound to light via microphone; master/slave function; DMX; stand-alone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	38°
Beam angle (1/2 peak):	38°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 68.5 cm Depth: 16.5 cm Height: 20.0 cm
Weight:	6.20 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery